

## Features

### CAR 2 CAR Communication Consortium



#### About the C2C-CC

Enhancing road safety and traffic efficiency by means of Cooperative Intelligent Transport Systems and Services (C-ITS) is the dedicated goal of the CAR 2 CAR Communication Consortium. The industrial driven, non-commercial association was founded in 2002 by vehicle manufacturers affiliated with the idea of cooperative road traffic based on Vehicle-to-Vehicle Communications (V2V) and supported by Vehicle-to-Infrastructure Communications (V2I). The Consortium members represent worldwide major vehicle manufactures, equipment suppliers and research organisations.

Over the years, the CAR 2 CAR Communication Consortium has evolved to be one of the key players in preparing the initial deployment of C-ITS in Europe and the subsequent innovation phases. CAR 2 CAR members focus on wireless V2V communication applications based on ITS-G5 and concentrate all efforts on creating standards to ensure the interoperability of cooperative systems, spanning all vehicle classes across borders and brands. As a key contributor, the CAR 2 CAR Communication Consortium and its members work in close cooperation with the European and international standardisation organisations.

#### Disclaimer

The present document has been developed within the CAR 2 CAR Communication Consortium and might be further elaborated within the CAR 2 CAR Communication Consortium. The CAR 2 CAR Communication Consortium and its members accept no liability for any use of this document and other documents from the CAR 2 CAR Communication Consortium for implementation. CAR 2 CAR Communication Consortium documents should be obtained directly from the CAR 2 CAR Communication Consortium.

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media. © 2021, CAR 2 CAR Communication Consortium.

---

## Document information

---

|                        |          |                 |      |                       |            |
|------------------------|----------|-----------------|------|-----------------------|------------|
| <b>Number:</b>         | 2036     | <b>Version:</b> | n.a. | <b>Date:</b>          | 2021-12-17 |
| <b>Title:</b>          | Features |                 |      | <b>Document Type:</b> | RS         |
| <b>Release</b>         | 1.6.1    |                 |      |                       |            |
| <b>Release Status:</b> | Public   |                 |      |                       |            |
| <b>Status:</b>         | Final    |                 |      |                       |            |

**Table 1: Document information**

**Changes since last version**

| Title:     | Features                |                    |                    |
|------------|-------------------------|--------------------|--------------------|
| Date       | Changes                 | Edited by          | Approved           |
| 2021-12-17 | No changes              | Release Management | Steering Committee |
| 2021-07-23 | Minor editorial changes | Release Management | Steering Committee |
| 2021-03-12 | No changes              | Release Management | Steering Committee |
| 2020-12-16 | Minor editorial changes | Release Management | Steering Committee |
| 2020-07-31 | Minor corrections       | Release Management | Steering Committee |
| 2020-03-27 | Minor corrections       | Release Management | Steering Committee |
| 2019-09-13 | Minor corrections       | Release Management | Steering Committee |
| 2018-08-31 | Minor corrections       | Release Management | Steering Committee |

**Table 2: Changes since last version**

## Table of contents

|                                 |   |
|---------------------------------|---|
| About the C2C-CC .....          | 1 |
| Disclaimer .....                | 1 |
| Document information .....      | 2 |
| Changes since last version..... | 3 |
| Table of contents.....          | 4 |
| List of tables .....            | 4 |
| 1 Introduction .....            | 5 |
| 2 Scope.....                    | 6 |
| 3 Conventions used.....         | 7 |
| 4 Definitions .....             | 8 |
| 5 Feature specification .....   | 9 |

## List of tables

|                                           |   |
|-------------------------------------------|---|
| Table 1: Document information.....        | 2 |
| Table 2: Changes since last version ..... | 3 |

---

## 1 Introduction

### Other (informational)

RS\_FEA\_147

Within the open system architecture of Cooperative Intelligent Transport System (C-ITS) four types of participants, called sub-systems, are identified in [EN 302 665]: vehicle, roadside, personal, and central. Each of these sub-systems includes a C-ITS station, but based on their sub-system specific equipment they enable different features. As a result of their feature list and their role in traffic, for each sub-system a set of use cases becomes possible to improve road safety and traffic efficiency.

---

## 2 Scope

### Other (informational)

**RS\_FEA\_146**

The present document provides all features in scope of a vehicle sub-system from C2C-CC point of view. This set of features is the consolidated and communicated understanding of the core vehicle system features in a vehicle C-ITS station. According to the C2C-CC contract, the present list focuses on specifying the vehicle C-ITS station transmitting side. Moreover, this set is oriented towards enabling the vehicle use cases as included in the current C2C-CC release. Details about the content of the release can be found in [C2CCC ReIOv] and are listed in brief in the following:

- emergency vehicle warning
- dangerous situation
- stationary vehicle warning
- traffic jam ahead warning
- collision risk (exchange of IRCs)
- adverse weather conditions

The use cases as part of the current C2C-CC release do not constitute a mandatory set of applications to be implemented as part of a vehicle C-ITS station. Only a subset of them might be supported by a specific implementation of the vehicle C-ITS station.

In terms of C2C-CC a feature defines a service or a major part of the vehicle C-ITS station. They always detail an objective, but – like objectives – without any further specification about its details. As a result, features are not directly testable.

Features itself are detailed by one or more requirements. A feature can be assumed as tested, if all requirements, which detail this feature, are tested.

---

## 3 Conventions used

### Other (informational)

RS\_FEA\_152

Conventions used in this and other C2C-CC specification documents can be found in [C2CCC ConV].

---

## 4 Definitions

**Definition**

**RS\_FEA\_149**

A vehicle C-ITS station is a vehicle ITS station as defined in [EN 302 665] and further specified in this C2C-CC release.

**Definition**

**RS\_FEA\_427**

'*Vehicle states*' comprise absolute position, heading and speed at a certain point in time.

**Definition**

**RS\_FEA\_428**

Information provided with a '*confidence level*' of 95 % means that the true value is inside the confidence interval for at least 95 % of the data points in a given statistical base.



## 5 Feature specification

**Feature** **RS\_FEA\_176**

AT changeovers shall be triggered in such a manner that at least 95 % of all trips are divided into three segments: A start segment in the beginning of a trip, an end segment and a middle segment in between.

Details:

Detailed by:

**Feature** **RS\_FEA\_405**

The vehicle C-ITS station shall support services for confidentiality within the communication with the PKI entities.

Details:

Detailed by:

**Feature** **RS\_FEA\_189**

The vehicle state estimation (see RS\_FEA\_427) shall include confidence intervals for the defined confidence level of 95% according to the definition in RS\_FEA\_428, as a standardized description of the estimation accuracy.

Details:

Detailed by:

**Feature** **RS\_FEA\_430**

The vehicle C-ITS station shall provide services for communicating with other C-ITS stations by using ITS-G5, operating in the frequency band 5855 MHz to 5925 MHz.

Details:

Detailed by:

**Feature** **RS\_FEA\_431**

The vehicle C-ITS station shall provide services to avoid channel congestion of the shared media.

Details:

Detailed by:

**Feature** **RS\_FEA\_432**

The vehicle C-ITS station shall provide mitigation techniques to avoid disturbing other services operating at nearby frequencies (i.e. CEN DSRC).

Details:

Detailed by:

**Feature** **RS\_FEA\_433**

The vehicle C-ITS station shall provide services for transmitting, receiving and forwarding messages to multiple, geographically scattered and movable entities.

Details:

Detailed by:

---

**Feature**

**RS\_FEA\_434**

The vehicle C-ITS station shall provide services for handling multiple messages of different types on the sender side.

Details:

Detailed by:

---

**Feature**

**RS\_FEA\_435**

The vehicle C-ITS station shall provide services for regularly transmitting information about itself and receiving of those information from other C-ITS stations in its vicinity.

Details:

Detailed by:

---

**Feature**

**RS\_FEA\_436**

The vehicle C-ITS station shall provide services for transmitting information about events on demand and receiving of those events from other C-ITS stations.

Details:

Detailed by:

---

**Feature**

**RS\_FEA\_437**

The vehicle C-ITS station shall use a standardized message format for each message type it exchanges with other C-ITS stations.

Details:

Detailed by:

---

**Feature**

**RS\_FEA\_438**

The vehicle C-ITS station shall check relevant host vehicle dynamics data (e.g. position, speed, heading, longitudinal acceleration, yaw rate) for plausibility.

Details:

Detailed by: RS\_BSP\_431, RS\_BSP\_514

---

**Feature**

**RS\_FEA\_439**

The vehicle C-ITS station shall use certificates (Authorization Tickets) and signatures to ensure authentication of message originator.

Details:

Detailed by: RS\_BSP\_160

---